



Pearl

Overview

This unique material is just as luxurious as its name. Solvent and UV compatible on the coated side and dye-sub transfer compatible on the uncoated side. The translucency of Decoprint Pearl is perfect for lighted displays, reflective or backlit. The soft hand and easy drape make it a good choice for POP, trade-show, custom table cloths and other applications.

Physical Properties

<u>Property</u>	<u>Unit</u>	<u>Test Method</u>
Weight:	4 oz. / sq. yd 135 g / sq. m	ASTM D3776-96
Tensile Strength:	200 / 190 lbf [warp/fill]	ASTM D2261-96
Material:	100% Woven Polyester	
Thickness:	0.00512 inches (5.1 mil) 0.13 mm	
Coating Color:	White	
Substrate Color:	White	
Printable Sides:	1	
Fire Rating	Permanent fire retardant M1 classification	
Width:	61" & 122"	
Length:	Rolls:	55 yds

Printability Key

Solvent	■	On coated side
*UV	■	On either side
Lithographic	□	
Dye Sublimation	■	Transfer method on uncoated side

* Prints from UV printing can crack in creases or folds if subject to temperatures below 32° f. Care should be taken to roll prints for transportation.

<u>Item#:</u>	<u>Description:</u>
ASTDECO0212255	AURORA DECO 02 PEARL 4Z 122X55
ASTDECO02A6155	AURORA DECO 02A PEARL 4Z 61X55

Although all data here is believed to be accurate, each user is advised to make their own determination as to whether the described product is appropriate for a particular application or use. Whether such a use will comply with all applicable laws or regulations and whether such use will not infringe the intellectual property rights of a third party.



www.SourceOneOnline.com

Regional Phone Numbers:

West: 800.252.7767

Midwest: 800.736.7636

Northeast: 800.257.8226

Southeast: 800.537.4606

Mexico: 011.525.55.576.6667